

Visqueen Detailing Strip



- **Ideal for complex junctions and stanchions**
- **Superior adhesion helps correct installation**
- **Use with unique Visqueen HP Tanking Primer Solution to obtain best performance**

Description

A white surfaced, self adhesive strip, supplied in 300mm x 10m rolls.

Application

Self adhesive strip to ensure continuity of damp protection at complex junctions and stanchions.

Visqueen Detailing Strip

Installation

Ensure surfaces are smooth, clean and dry. Prime the substrate to which the strip is to be adhered with Visqueen Tanking Primer and allow to dry. Do not apply primer to surface of membrane. Cut the strip to size ensuring overlap of minimum 150mm on to the membrane and the primed substrate. Progressively remove the release paper while pressing the strip firmly on to the surface. Work from the centre of the strip outwards to remove any trapped air. When the weather is cold, store strip in a warm, dry place until required. Installation is not recommended below 5C.

TYPICAL PROPERTIES

Technical Data

Roll Width	300mm
Roll Length	10m
Methane Gas Resistance	<0.03mls/m ² /d
Visqueen HP Tanking Primer	
Dry Time	1-5 hours at normal temperature
Application rate - concrete	6-8m ² /l
Availability	5L

The information given in this datasheet is based on data and knowledge correct at the time of printing. Statements made are of a general nature and are not intended to apply to any use or application outside any referred to in the datasheet. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.

SPECIFICATION SUPPORT

The following items are available to view online or to download from www.visqueenbuilding.co.uk

- . Technical Datasheets
- . Typical installation CAD details
- . Health and Safety data

Register online for access to NBS Clauses and for information about our CPD Seminars



TECHNICAL SUPPORT

For advice on detailing or installation call Visqueen Building Products Technical Help Line 0845 302 4758. Pricing & Availability may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 0845 302 4758.

VISQUEEN

BUILDING PRODUCTS

Heanor Gate, Heanor, Derbyshire DE75 7RG

T: 0845 302 4758 F: 0845 017 8663

enquiries@visqueenbuilding.co.uk

www.visqueenbuilding.co.uk

VISQUEEN BUILDING PRODUCTS IS A TRADING NAME OF BRITISH POLYTHENE LIMITED, COMPANY NUMBER: 350729, REGISTERED OFFICE: ONE LONDON WALL, LONDON, EC2Y 5AB