

VisqueenPro Single Sided Jointing Tape

Page 1 of 2



- Twice the adhesive strength of rival tapes
- Independently tested for peel and adhesion
- Crossweave film for excellent anti-tear properties
- Part of the BBA approved DPM Jointing system

Description

A cross weave glass fibre reinforced tape coated with a high tack aggressive adhesive system for sealing laps in damp proof membranes. When used in conjunction with Visqueen Double Sided Jointing tape, the system performs a BBA (Cert 94/3009) approved watertight seal.

Application

VisqueenPro Single Sided Jointing tape is for sealing Visqueen Damp Proof Membranes at overlaps and for sealing membranes to Visqueen Damp Proof Courses at junctions with internal and external walls.

Peel Adhesion

VisqueenPro Single Sided Jointing Tape peel adhesion testing was conducted to BS EN 60454-2 2007 at an independent UKAS accredited test house at two temperatures - 23oC and 5oC. Five alternative tapes including a PP and cloth were also tested.

The results are shown on the table below. The test results indicated that VisqueenPro Single Sided Tape had twice the adhesive strength of the nearest alternative.

VisqueenPro Single Sided Jointing Tape

Page 2 of 2

Installation

Ensure surfaces are clean and dry. Apply tape equidistant over the bonded membrane lap. Apply pressure to the tape to ensure adhesion. When the weather is cold, store tape in a warm, dry place until required. Installation is not recommended below 5oC.

TYPICAL PROPERTIES

Technical Details

Width	75mm
Length	25m
Total Thickness	0.125mm
Tensile strength	240 N/cm
Peel Adhesion BS EN 60454-2 2007 - 23oC	1.68 N/mm
Peel Adhesion BS EN 60454-2 2007 - 5oC	1.69 N/mm

The information given in this datasheet is based on data and knowledge correct at the time of printing. Statements made are of a general nature and are not intended to apply to any use or application outside any referred to in the datasheet. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.

SPECIFICATION SUPPORT

The following items are available to view online or to download from www.visqueenbuilding.co.uk

- . Technical Datasheets
- . Typical installation CAD details
- . Health and Safety data

Register online for access to NBS Clauses and for information about our CPD Seminars



TECHNICAL SUPPORT

For advice on detailing or installation call Visqueen Building Products Technical Help Line 0845 302 4758. Pricing & Availability may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 0845 302 4758.

VISQUEEN

BUILDING PRODUCTS

Heanor Gate, Heanor, Derbyshire DE75 7RG

T: 0845 302 4758 F: 0845 017 8663

enquiries@visqueenbuilding.co.uk

www.visqueenbuilding.co.uk

VISQUEEN BUILDING PRODUCTS IS A TRADING NAME OF BRITISH POLYTHENE LIMITED, COMPANY NUMBER: 350729, REGISTERED OFFICE: ONE LONDON WALL, LONDON, EC2Y 5AB