

Paslode Impulse IM350+ Gas Framing Nailer

The IM350+ gas framing nailer is the UK's market leading first fix tool. Paslode's unrivalled gas technology provides more reliability, increased accuracy and extended service levels.



Includes:

Paslode Impulse IM350+ Framing Nailer, high impact carry case, 2 x batteries, battery charger, AC / DC adaptor, cleaning solution, Impulse lubricant, safety glasses with EN166:F, allen key and instruction manual.

Eurocode & Description

Eurocode: 014801 **Box Qty**
IM350+ Framing Nailer 1

ALSO AVAILABLE



Paslode Impulse Naked IM350+
Eurocode: 014808 **Box Qty**
NAKED IM350+ Framing Nailer 1
(Includes Tool ONLY)

Technical Specification

Weight: 3.4kg
Dimensions: 370 x 305 x 110mm
Nail range: 51 - 90mm
Power: 82J
Cycle rate: 2 - 3 nails / second
Max. cycle rate: 1,000 nails / hour
4,000 nails / day
Magazine: 55 nails
Fuel cell life: Approx. 1,100
Battery NiCd: Approx. 4,000
(1.2 Ah 6V) per charge
Charger 230V: 2 hours max. charge

Substrates

- Wood

Features and Advantages

- **Non-slip soft grip handle** - User comfort and reduced user fatigue
- **Nose probe with added teeth** - Helps bite into the timber to ensure positive placement of the nail
- **Dual action rafter/belt hook** - To withstand site abuse
- **Low actuation force** - Reduced user fatigue
- **Follower guide** - Easier nail loading
- **Pinch and slide depth of drive adjuster** - Ease of use



Nose probe



Soft grip handle



Rafter / belt hook



Pinch and slide depth of drive

Nail Specification

Finishes / Material:

- Bright (BR)
- GALV-PLUS®
- Hot Dipped Galvanised (HDGV)
- Stainless Steel (S/STEEL)

Point Types:

Diamond Point

Head Types:

Clipped Head

Collation Types:


Paper Strip

Shank Types:

RG - Ring Shank 2.8 / 3.1mm



UNI - Unilock 3.1mm




ST - Smooth Shank 3.1mm



IM350+ Nail Fuel Packs



INDOORS - Eurocode 5 Service Class 1



Eurocode	Length	Nail Ø	Shank Type / Finish	Fuel Cells	Box Qty	Box Size*
141202	51mm	2.8mm	RG BR	3	3,300	M
141208	63mm	2.8mm	RG BR	3	3,300	M
141226	75mm	3.1mm	RG BR	2	2,200	M
141271	90mm	3.1mm	ST BR	1	1,100	S
141233	90mm	3.1mm	ST BR	2	2,200	M

INDOORS NOT HEATED, OUTDOORS PROTECTED - Eurocode 5 Service Class 1 & 2



Eurocode	Length	Nail Ø	Shank Type / Finish	Fuel Cells	Box Qty	Box Size*
141256	51mm	2.8mm	RG GALV-PLUS	1	1,100	S
141204	51mm	2.8mm	RG GALV-PLUS	3	3,300	M
141259	63mm	2.8mm	RG GALV-PLUS	1	1,100	S
141210	63mm	2.8mm	RG GALV-PLUS	3	3,300	M
141263	63mm	3.1mm	RG GALV-PLUS	1	1,100	S
141221	63mm	3.1mm	RG GALV-PLUS	2	2,200	M
141227	75mm	3.1mm	RG GALV-PLUS	2	2,200	M
141234	90mm	3.1mm	ST GALV-PLUS	2	2,200	M

OUTDOORS, EXPOSED TO WEATHER - Eurocode 5 Service Class 1, 2 & 3



Eurocode	Length	Nail Ø	Shank Type / Finish	Fuel Cells	Box Qty	Box Size*
141260	63mm	2.8mm	RG HDGV	1	1,100	S
141211	63mm	2.8mm	RG HDGV	3	3,300	M
141222	63mm	3.1mm	RG HDGV	2	2,200	M
141265	75mm	3.1mm	RG HDGV	1	1,100	S
141228	75mm	3.1mm	RG HDGV	2	2,200	M
141267	90mm	3.1mm	ST HDGV	1	1,100	S
141235	90mm	3.1mm	ST HDGV	2	2,200	M
141236	90mm	3.1mm	UNI HDGV	2	2,200	M
141257	51mm	2.8mm	RG S/STEEL	1	1,100	S
141261	63mm	2.8mm	RG S/STEEL	1	1,100	S
141266	80mm	3.1mm	RG S/STEEL	1	1,100	S



Applications

- Timber frame
- Truss work
- Stud work
- Roof battening
- Cladding
- Joists
- Floor boarding
- Noggins
- Overboarding
- Soffits
- Roof decking
- Roofing
- Fencing
- Shuttering
- Packaging
- Hoarding
- Decking
- Close boarding

Noise / Vibration Information

Noise Emissions: Measured values determined according to EN 12549.

$L_{PA,1s,1m}$ 96 dB (A) Sound pressure

$L_{WA,1s}$ 110 dB (A) Sound power

L_{pCpeak} 138 dB (C)

Measured according to EN ISO 8662-11

HAV: The typical weighted acceleration does not exceed **2.6m/s²**.

Accessories: Refer to page 59 for full list

Eurocode	Description	Qty
012082	IM350+ No Mar Work Contact Element	1
404717	Impulse Battery Cell	1
035460	Charger Base	1
900506	AC / DC Adaptor	1
900200	Battery Charger with AC / DC Adaptor	1
900507	In-car Charger Adaptor	1
014121	Safety Goggles with EN166 (B & F markings)	1
013060	Impulse Cleaning Kit	1
401482	Impulse Lubricating Oil	1
115251	Impulse / Pulsa Cleaner	1
300346	Paslode Impulse Standard Fuel Cell Blister Pack of 2	1

* Box Size:

S = Handy Pack



M = Nail Fuel Pack



IM350+ Fuel Cell

Special Impulse gas fuel cell(s) are included in all Nail Packs.



Nail Selection Guide

NAIL SIZE	APPLICATIONS	APPLICATIONS										
		Floor boarding	Stud work	Noggin	Joist	Timber frame	Roof battening	Close boarding	Roof decking	Decking	External cladding	Fencing
BRIGHT	51 x 2.8mm RG	●										
	63 x 2.8mm RG	●										
	75 x 3.1mm RG		●	●								
	90 x 3.1mm ST		●	●	●							
GALV-PLUS®	51 x 2.8mm RG							●				
	63 x 2.8mm RG	●						●				
	63 x 3.1mm RG							●				
	90 x 3.1mm ST		●	●	●							
HDGV	63 x 2.8mm RG							●		●		
	63 x 3.1mm RG							●		●		
	75 x 3.1mm RG							●		●		
	90 x 3.1mm ST							●		●		
S/STEEL	51 x 2.8mm RG							●		●	●	
	80 x 3.1mm RG							●		●	●	

- BR - BRIGHT
- GALV-PLUS®
- HDGV - HOT DIPPED GALV
- S / STEEL - STAINLESS STEEL

No coating - Indoor use ONLY
 Medium duty protection - 15 microns galvanising
 Heavy duty protection - 55 microns galvanising
 For extreme applications