

NEW Paslode Impulse IM65 F16

LITHIUM Gas Brad Nailer

The Paslode IM65 F16 Lithium Cordless Brad Nailer boasts a new quick charge battery system, improved weight and balance and adjustable depth of drive, making it the best solution for second fix timber applications.



Includes:

Paslode Impulse IM65 Brad Nailer, high impact carry case, LITHIUM battery, LITHIUM battery charger, cleaning solution, short brads kit for IM65, lubricating oil, safety glasses to EN166:F, allen key, safety instructions, CE Declaration of Conformity, tool schematics and instruction manual

Eurocode & Description

Eurocode: 013323 **Box Qty**
IM65 F16 Lithium Brad Nailer 1

Technical Specification

Weight: 2.1kg
Dimensions: 301 x 288 x 90mm
Power: 30J
Brad range: 16mm - 63mm
Cycle rate: 2 - 3 brads / second
Maximum cycle rate: 1,000 brads / hour
4,000 brads / day
Magazine: 100 brads
Fuel cell life: Approx. 1,000
Battery LITHIUM: Up to 6,000 per charge
1.25 Ah
Charger 230V: 1 hour max. charge

Substrates

- Softwood and Hardwood
- MDF and similar substrates
- Laminates

Features and Advantages

- **Quick charge, long life lithium battery** - With an improved on/off battery system the new Lithium battery fires up to 6000 brads on a single charge (1 hour); 200 brads in just 2 minutes charge
- **Improved weight & well balanced** - Allows any user to manoeuvre into tight spaces and work without fatigue all day long
- **Reversible belt hook** - Easy access when not in use
- **Over 25 years of gas tool expertise** - has resulted in this fourth generation industry leading tool. Every tool is produced and tested in Europe before shipment
- **Consistent excellent finishing** - Improved adjustable Depth of Drive produces required embedment every time
- **No-mar tip** - For accurate placement and reduced damage to wood



Quick charge, long life lithium battery



Improved weight & balance



Tool free depth adjuster



On / off position

Brad Specification

Finishes / Material:

- Stainless Steel
- Electro Galvanised

Brad Gauges:

F16 Wire size 1.6mm

Point Types:

Chisel Point

Head Types:

Lost Head 

Collation Types:

Glued, Straight



Applications

- Door stops
- Tongue and Groove panelling
- Architraves
- Window casing
- Dado rail
- Skirting boards
- Beading
- Stair rails
- MDF fixing

Noise / Vibration Information

Noise Emissions: Measured values determined according to EN 12549.

$L_{PA,1s,1m}$ 90 dB (A) Sound pressure

L_{pCpeak} 128 dB (C)

Measured according to EN ISO 8662-11

HAV: The typical weighted acceleration does not exceed **2.5m/s²**.

Accessories: Refer to page 59 for full list

Eurocode	Description	Qty
300341	Mini Fuel Cell Blister Pack Yellow (Pack of 2)	1
018880	LITHIUM Battery	1
018882	LITHIUM Battery Charger	1
012027	Panelling Probe	1
219236	Nose Tip (3 pack)	1
900507	In-car Charger Adaptor	1
014975	Trim Tool Carry Case	1
014121	Safety Glasses to EN166:F	1
401482	Impulse Lubricating Oil	1
115251	Impulse Cleaner 300ml	1
013060	Impulse Cleaning Kit	1

* Available in Q4 2013

Brad Fuel Packs

F16 Brad Fuel Packs for IM65 F16 and IM250



ELGV



S/STEEL

Eurocode	Gauge	Length	Finish	Fuel Cells	Box Qty
921585	F16	16mm	ELGV	2	2,000
921586	F16	19mm	ELGV	2	2,000
921587	F16	25mm	ELGV	2	2,000
921588	F16	32mm	ELGV	2	2,000
921589	F16	38mm	ELGV	2	2,000
921590	F16	45mm	ELGV	2	2,000
921591	F16	50mm	ELGV	2	2,000
921592	F16	63mm	ELGV	2	2,000
921593	F16	25mm	S / STEEL	2	2,000
921594	F16	38mm	S / STEEL	2	2,000
921595	F16	50mm	S / STEEL	2	2,000
921596	F16	63mm	S / STEEL	2	2,000

Please Note: Stainless Steel is Grade A2 - 304

IM65/65A Mini Fuel Cell (Yellow)

Mini Impulse gas fuel cells are included in Brad Fuel packs.



2 x Mini fuel cells per pack

Brad Selection Guide

BRAD SIZE	APPLICATIONS							
		Dado rail	Architrave	Skirting	Beading	Door stop	MDF fixing	Hardwood
ELGV	F16 x 16mm							
	F16 x 19mm							
	F16 x 25mm							
	F16 x 32mm							
	F16 x 38mm							
	F16 x 45mm							
	F16 x 50mm							
	F16 x 63mm							
S / STEEL	F16 x 25mm							
	F16 x 38mm							
	F16 x 50mm							
	F16 x 63mm							

● ELGV - ELECTRO GALVANISED Light duty protection - 1-3 microns galvanising

● S / STEEL - STAINLESS STEEL For extreme applications